

L Number	Hits	Search Text	DB	Time stamp
15	497	Shawn with "O'Hara") (William with Chapman) (Yee with Ng	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:03
16	2	(Shawn with "O'Hara") (William with Chapman) (Yee with Ng) and jtag	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:04
17	1	(Shawn with "O'Hara") (William with Chapman) (Yee with Ng) and (delay same jtag)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:04
18	10	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (jtag (joint with test)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:15
19	1	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and (coarse with (adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and (fine with (adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (jtag (joint with test)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:12
20	1	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (jtag (joint with test))) and (bow)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:14
21	0	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) same substrate same image same (driver driving) same pixel) and (((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) same delay same (jtag (joint with test)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:15
22	1	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and bow	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:16
24	0	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) same substrate same image same (driver driving) same pixel) and (((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) same delay same (led diode))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:17
23	48	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (led diode))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:25

25	7	(printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (led diode) and (jtag (delay with (linear linearity)))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:27
26	1	(printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (led diode) and (jtag (delay with (linear linearity))) and bow	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:27
27	1	(printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (led diode) and bow	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:27
28	1	((printhead ((print printer printing recording recorder inkjet (ink with jet)) with head)) and substrate and image and (driver driving) and pixel and ((adjust adjusting adjustment correct correcting correction) with (circuit circuitry)) and delay and (led diode)) and (bow with (correct correcting correction adjust adjusting adjustment))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/06/10 12:28